

The Antikor Dual Layer (Layer2 & Layer3) SD-WAN EPA-TN-8 Series is a Turkish national product that provides secure virtual switching at the Layer2 level in SMB networks with advanced network and security features. Thanks to its bonding feature, it transfers different types of internet (xDSL, 4.5G, metro, asymmetric fiber, etc.) to the center simultaneously. It can perform packet filtering (Layer2 Firewall) and QoS - Active Bandwidth Management in traffic.

Layer2 Communication over WAN



By extending our local network over our internet connections, we create a closed network by performing secure virtual switching (virtual switching) at the Layer2 level. It works as an uplink between switches. In short, the broadcast domains of both networks are merged.

Multiple VLAN transfer in WAN



In the Antikor Dual Layer SD-WAN solution, independent isolated Virtual Switches can be created, and they are transferred encrypted with the assigned VLANs on the other side. It allows for MAC-IP matching control.

Switching and Compatibility




Both Virtual Ports and Physical Ports have the IEEE 802.1Q VLAN feature (Untagged Port Assignment, Tagged Port Assignment and Hybrid Port Assignment). It has High Availability Cluster (Active-Passive Cluster) and Fail-over features.

Central Management and Logging



Through the Central Management System and monitoring, bulk settings can be obtained. It sends logs to all SIEM solutions in RAW, CEF, EWMM, GELF, JSON, WELF, CIM formats. It has LACP, LLDP, and Netflow Export services.





Product Specifications

Operating Modes

Traffic Capturing on:

- OSI Layer 2 - Ethernet

Tunneling over:

- OSI Layer 3 - IPv4 & IPv6
- OSI Layer 3 - Working Behind NAT

Virtual Switch Features

Assigning Layer2 Tunnels as Virtual Ports

IPsec Encryption for Layer2 Tunnels

Physical Port Assignment

IEEE 802.1Q VLAN for both Virtual and Physical Ports:

- Untag Port Assignment
- Tagged Port Assignment
- Hybrid Port Assignment

VLAN Enabled MAC Table

IEEE 802.3ad Link Aggregation Control Protocol (LACP)

Spanning Tree Protocol

Rapid Spanning Tree Protocol

Link Layer Discovery Protocol

NetFlow Export Service

MAC Learning

Ethernet Interface Specifications

4094 IEEE 802.1Q VLANs for each port

IEEE 802.3ad LACP

Virtual Ethernet Interface

- Loopback
- VLAN subinterface

IPsec VPN

Encryption: DES, 3DES, AES, BLOWFISH, CAST128, CAMILIA

Authentication: MD5, SHA1, SHA256, SHA384, SHA512, 3DES, DES

Wildcard ID Support

NAT Traversal Support

Assigning different IPsec Profiles for each Layer2 Tunnel

Management Interface Features

HTML5 Responsive Web Interface

- SSL Certificate based authentication
- Customizing the service port

Out of Band Management Plane

SSH Console

Physical Console (Monitor, Keyboard)

System Performance

MAC Table Size	8
Layer2 Throughput (Gbps)	50 Mbps
Firewall Throughput (Gbps)	25 Mbps
IPsec Throughput (Gbps)	10 Mbps

Licensing

Number of Layer2 Tunnels	1
Number of Phys. Ports can be Assigned to a Virtual Switch	2
Number of Tunnels can be Assigned to a Virtual Switch	1
Number of VLANs for Layer2 Tunnels	1
High Availability (HA) - Cluster Support	No
Number of Addressable CPU Threads	2
Number of IPsec VPN Tunnels	1
Number of Virtual Switches	1
IEEE 802.3ad LACP Support on Virtual Switches	No
WAN Bonding	No
MTU Adaptation for WAN	Yes

Services

Live Dashboard

Automated Update System

WAN Bonding (Optional)

SNMP v2/v3 Service

Layer2 Packet Filtering on Tunneled Traffic (Optional)

QoS - Quality of Service on Tunneled Traffic (Optional)

Port Grouping

Syslog Service (RAW, CEF, EWMM, GELF, JSON, WELF, CIM)

MAC Learning

Authorization Management

Isolated Virtual Switching

NetFlow Export Service

Incident Notification Service

- SMS, Email, Browser Notification

Routing

IPv4 / IPv6 Static Routing

OSPF(Open Shortest Path First), BGP(Border Gateway) Protocols

Hardware Requirements

Min 2 Core Processor

Min 2 GB Ram

Min 64 GB Solid State Disc

Min 2 x Gigabit Ethernet Card

* Performance tests are performed with the following hardware:

- Intel Atom E3940 Processor, 4 GB DDR3L 1866 MHz RAM

** Note: All performance values may vary depending on environmental conditions, system configuration and equipment.

eP-FR-79 Rev.02 / Release date: 01.04.2019 / Rev.date: 02.05.2021

ePati Cyber Security Technologies Inc.

Mersin Universitesi Ciftlikkoy Kampusu

Teknopark Idari Binasi Kat: 4 No: 411

Zip Code: 33343 Yenisehir / MERSIN / TURKIYE

www.epati.com.tr

info@epati.com.tr

+90 324 361 02 33

+90 324 361 02 39

